


STYLE BABSL HIGH PRESSURE SHAFT SEALS



Ordering Information

Part Number: MOS - d1 x d2 x b BABSL or BABSLV

Sizes and styles are in stock where prices are shown.

	BABSL	
	SHAFT SEAL	
	MATERIAL	NITRILE 72 SHORE A
	TEMPERATURE RANGE	-40° TO +212° F
	PRESSURE RANGE	0 TO 145 PSI

	BABSLV	
	SHAFT SEAL	
	MATERIAL	FLUOROCARBON 75 SHORE A
	TEMPERATURE RANGE	-40° TO +320° F
	PRESSURE RANGE	0 TO 145 PSI

d1 (ID)	d2 (OD)	b (HT)	b1 (OAHT)	BABSL	BABSLV
8	22	6	2.78	\$ 12.86	\$ 44.37
10	22	6	2.78	13.41	51.15
12	22	6	2.78	13.95	51.15
12	24	6	2.78	14.50	44.37
15	35	6	4.62	15.03	52.16
18	35	6	2.78	15.65	52.16
20	35	6	4.62	16.29	65.93
22	32	6	4.62	16.91	68.00
22	35	6	4.62	17.52	69.77
25	35	6	4.62	18.14	73.27
25	47	6	4.62	18.76	73.73
28	40	6	4.62	20.24	93.94
30	42	6	4.62	17.56	100.47
35	52	6	2.78	19.70	125.52
40	62	6	4.62	22.16	148.05
45	58	7	2.78	27.06	
45	62	7	4.62	24.40	149.19
50	72	7	4.62	26.31	167.36
60	80	7	4.62	28.83	186.67
62	85	7	4.62	40.29	202.47
70	90	7	6.43	34.61	211.58
80	100	7	8.83	37.10	237.01
85	105	7.5	6.43	40.23	
90	110	7.5	5.75	62.32	296.34
100	120	7.5	5	81.38	316.51

BABSL and BABSLV Rubber Covered OD, Double Lip, High Pressure Oil Seal

Design Series BABSL has an extremely short, flexibly suspended sealing lip for sealing pressurized media without a backup ring. It also has a second lip for additional dust protection.

FOR OPERATING PRESSURE
UP TO 4 BAR (50 PSI)

Specifically designed for rotational pressure sealing. e.g. hydraulic pumps, hydraulic motors, hydrodynamic clutches & transmissions, heating oil pumps.